

Description and Quantity of Open File Shelving Equipment Required.

<u>Item</u>	<u>Quantity</u>
Initial single face section	4
Additional single face section	5
Single face dust canopy	9
Single face end panel	8
Receding reference shelf	4

Equipment is to be assembled and installed by the successful bidder to form 3 ranges of 2 single-faced sections and 1 range of 3 single-faced sections. Dimensions: height of uprights to be 84" to provide a 3" base and 7 shelf openings not less than 10 $\frac{1}{2}$ " from the filing surface of one shelf to the lowest projection of the next higher shelf or the dust canopy. Filing capacity of each shelf is to be not less than 34 $\frac{1}{2}$ " when equipped with 5 removable shelf partitions. The dust canopies and end panels are to be attached in a manner not to interfere with the normal operation of the equipment. For detailed specifications relative to the formation of the integral parts and the gauges of steel, use the descriptive material developed for procurement order number 57-7365 with the following changes and modifications.

- a. Required quantity of shelf guides is fifty.
- b. The receding reference shelf is to be installed on the left-hand section of each of the three 2-section ranges and on the center section of the 3-section range on the underside of the fourth filing surface. The reference shelf shall provide a reference surface 30" wide by 13" deep. The reference shelf shall slide in a channel which engages the front and back underside formation of the shelf and does not interfere with the 10 $\frac{1}{2}$ " filing height of the next lower shelf. The reference shelf shall be generally designed the same as the adjustable shelf and of 18 gauge steel. Source of supply to be determined by the closed bid process.

2. Step Ladder, mounted on wheels

<u>Item</u>	<u>Quantity</u>
Model SS-20	1
Width 21"	
Length 18 3/4"	
Top step height 18"	
Overall Height 22 3/4"	
Price (Approx.) \$54	

Source of Supply

25X1A5a1